

# Your Ultimate Source for OEM Repair Manuals

FactoryManuals.net is a great resource for anyone who wants to save money on repairs by doing their own work. The manuals provide detailed instructions and diagrams that make it easy to understand how to fix a vehicle.

## 2008 NISSAN Titan King Cab OEM Service and Repair Workshop Manual

[Go to manual page](#)

## 1. PERFORM DTC CONFIRMATION PROCEDURE

---

 With CONSULT

1. Power switch ON and wait at least 2 seconds.
2. Check "Self diagnosis Results" of "HIGH VOLTAGE BATTERY" and "HIGH VOLTAGE BATTERY 2".

Is P1B67-F1 detected?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

Sample

## 1. CHECK CELL VOLTAGE DATA MONITOR

---

 With CONSULT

1. Power switch ON.
2. Select "Data Monitor" of "HIGH VOLTAGE BATTERY".
3. Select "Cell condition 01-96".
4. Check that each cell is abnormal.

Is any cell abnormal?

YES>>

[GO TO 2.](#)

NO>>

Perform intermittent incident. Refer to [Intermittent Incident](#).

## 2. CHECK CELL VOLTAGE DETECTION CIRCUIT

---

Check cell voltage circuit (harness connector between cell controller and module) corresponding to that cell is abnormal. Refer to [Diagnosis Procedure](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Is the inspection result normal?

YES>>

[GO TO 3.](#)

NO>>

Repair or replace malfunctioning parts.

## 3. CHECK CELL VOLTAGE

---

Check the voltage of the cell corresponding to abnormal cell number. Refer to [Component Inspection](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Cell voltage is 0.5 V or more>>

Replace cell controller corresponding to that cell is abnormal. Refer to [Removal & Installation](#).

Cell voltage is 0.5 V or less>>

Replace corresponding module. Refer to [Disassembly & Assembly](#).

**DTC DETECTION LOGIC**

DTC		CONSULT screen terms	DTC detection condition	
P1B67	F2	Cell voltage circuit (Module 8)	Diagnosis condition	Power switch ON
			Signal (terminal)	Cell voltage
			Threshold	When cell voltage falls below available voltage range
			Diagnosis delay time	2 seconds or less

**POSSIBLE CAUSE**

- Cell voltage detection circuit
- Cell (module)
- Cell controller

**FAIL-SAFE**

Not applicable

## 1. PERFORM DTC CONFIRMATION PROCEDURE

---

 With CONSULT

1. Power switch ON and wait at least 2 seconds.
2. Check "Self diagnosis Results" of "HIGH VOLTAGE BATTERY" and "HIGH VOLTAGE BATTERY 2".

Is P1B67-F2 detected?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

Sample

## 1. CHECK CELL VOLTAGE DATA MONITOR

---

 With CONSULT

1. Power switch ON.
2. Select "Data Monitor" of "HIGH VOLTAGE BATTERY".
3. Select "Cell condition 01-96".
4. Check that each cell is abnormal.

Is any cell abnormal?

YES>>

[GO TO 2.](#)

NO>>

Perform intermittent incident. Refer to [Intermittent Incident](#).

## 2. CHECK CELL VOLTAGE DETECTION CIRCUIT

---

Check cell voltage circuit (harness connector between cell controller and module) corresponding to that cell is abnormal. Refer to [Diagnosis Procedure](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Is the inspection result normal?

YES>>

[GO TO 3.](#)

NO>>

Repair or replace malfunctioning parts.

## 3. CHECK CELL VOLTAGE

---

Check the voltage of the cell corresponding to abnormal cell number. Refer to [Component Inspection](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Cell voltage is 0.5 V or more>>

Replace cell controller corresponding to that cell is abnormal. Refer to [Removal & Installation](#).

Cell voltage is 0.5 V or less>>

Replace corresponding module. Refer to [Disassembly & Assembly](#).

**DTC DETECTION LOGIC**

DTC		CONSULT screen terms	DTC detection condition	
P1B68	12	Cell voltage circuit (Module 9)	Diagnosis condition	Power switch ON
			Signal (terminal)	ASIC
			Threshold	When short circuit of cell voltage measuring circuit is detected.
			Diagnosis delay time	2 seconds or less

**POSSIBLE CAUSE**

- Cell voltage detection circuit
- Cell (module)
- Cell controller

**FAIL-SAFE**

Not applicable

## 1. PERFORM DTC CONFIRMATION PROCEDURE

---

 With CONSULT

1. Power switch ON and wait at least 2 seconds.
2. Check "Self diagnosis Results" of "HIGH VOLTAGE BATTERY" and "HIGH VOLTAGE BATTERY 2".

Is P1B68-12 detected?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

Sample



## 1. CHECK CELL VOLTAGE DATA MONITOR

---

 With CONSULT

1. Power switch ON.
2. Select "Data Monitor" of "HIGH VOLTAGE BATTERY".
3. Select "Cell condition 01-96".
4. Check that each cell is abnormal.

Is any cell abnormal?

YES>>

[GO TO 2.](#)

NO>>

Perform intermittent incident. Refer to [Intermittent Incident](#).

## 2. CHECK CELL VOLTAGE DETECTION CIRCUIT

---

Check cell voltage circuit (harness connector between cell controller and module) corresponding to that cell is abnormal. Refer to [Diagnosis Procedure](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Is the inspection result normal?

YES>>

[GO TO 3.](#)

NO>>

Repair or replace malfunctioning parts.

## 3. CHECK CELL VOLTAGE

---

Check the voltage of the cell corresponding to abnormal cell number. Refer to [Component Inspection](#).



**NOTE:**

For comparison of cell, module, and cell controller, Refer to [Component Description](#).

Cell voltage is 0.5 V or more>>

Replace cell controller corresponding to that cell is abnormal. Refer to [Removal & Installation](#).

Cell voltage is 0.5 V or less>>

Replace corresponding module. Refer to [Disassembly & Assembly](#).

**DTC DETECTION LOGIC**

DTC		CONSULT screen terms	DTC detection condition	
P1B68	13	Cell voltage circuit (Module 9)	Diagnosis condition	Power switch ON
			Signal (terminal)	ASIC
			Threshold	When open circuit of cell voltage measuring circuit is detected.
			Diagnosis delay time	2 seconds or less

**POSSIBLE CAUSE**

- Cell voltage detection circuit
- Cell (module)
- Cell controller

**FAIL-SAFE**

Not applicable