

Your Ultimate Source for OEM Repair Manuals

FactoryManuals.net is a great resource for anyone who wants to save money on repairs by doing their own work. The manuals provide detailed instructions and diagrams that make it easy to understand how to fix a vehicle.

2020 NISSAN Quest Service and Repair Manual

[Go to manual page](#)

1. CHECK DTC PRIORITY

If DTC “C1F56-82” is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#).

NO>>

[GO TO 2.](#)

2. PERFORM SELF-DIAGNOSIS OF ABS ACTUATOR AND CONTROL UNIT

Check if any DTC is detected in “Self Diagnostic Result” of “ABS”.

Is any DTC detected?

YES>>

Perform diagnosis on the detected DTC and repair or replace the malfunctioning parts. Refer to [DTC Index](#).

NO>>

Replace the ADAS control unit 2. Refer to [Removal and Installation](#).

DTC DETECTION LOGIC

DTC		CONSULT screen terms (Trouble diagnosis content)	DTC detection condition	
C1F56	83	EPS sub system circuit (Electric power steering sub system circuit)	Diagnosis condition	<ul style="list-style-type: none"> When vehicle is READY When AEB system is ON
			Signal (terminal)	—
			Threshold	If ADAS control unit 2 detects an error signal that is received from steering angle sensor via CAN communication
			Diagnosis delay time	1 second or less

POSSIBLE CAUSE

- Steering angle sensor
- ADAS control unit 2

FAIL-SAFE

The following system are cancelled.

- Lane keep function*
- Lane change support function
- Overtaking support function
- Route driving support function

*: ProPILOT Assist 2.0 display is blue

CONFIRMATION PROCEDURE

1. CHECK DTC PRIORITY

If DTC “C1F56-83” is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#).

NO>>

[GO TO 2.](#)

2. PERFORM DTC CONFIRMATION PROCEDURE

- Set the vehicle to READY.

2. Turn the AEB system ON.

3. Perform “All DTC Reading” with CONSULT.

4. Check if the “C1F56-83” is detected as the current malfunction in self-diagnosis results of “ICC/ADAS 2”.

Is “C1F56-83” detected as the current malfunction?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

Sample

1. CHECK DTC PRIORITY

If DTC “C1F56-83” is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#).

NO>>

[GO TO 2.](#)

2. PERFORM SELF-DIAGNOSIS OF ABS ACTUATOR AND CONTROL UNIT

Check if any DTC is detected in “Self Diagnostic Result” of “ABS”.

Is any DTC detected?

YES>>

Perform diagnosis on the detected DTC and repair or replace the malfunctioning parts. Refer to [DTC Index](#).

NO>>

Replace the ADAS control unit 2. Refer to [Removal and Installation](#).

DTC DETECTION LOGIC

DTC		CONSULT screen terms (Trouble diagnosis content)	DTC detection condition	
C1F76	49	Steering angle sensor (Steering angle sensor)	Diagnosis condition	<ul style="list-style-type: none"> When vehicle is READY When MAIN switch of ProPILOT Assist 2.0 system is ON
			Signal (terminal)	CAN communication signal
			Threshold	If the steering angle sensor is malfunction
			Diagnosis delay time	1 second or less

POSSIBLE CAUSE

- Steering angle sensor
- ADAS control unit 2

FAIL-SAFE

The following systems are canceled.

- Vehicle speed & vehicle-to-vehicle control function
- Lane keep function*¹
- Lane keep function*²
- Lane change support function
- Overtaking support function
- Route driving support function
- AEB
- RAB
- I-FCW
- I-BSI
- TSR

*1: ProPILOT Assist 2.0 display is green

*2: ProPILOT Assist 2.0 display is blue

CONFIRMATION PROCEDURE

1. CHECK DTC PRIORITY

If DTC "C1F76-49" is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#).

NO>>

[GO TO 2.](#)

2. PERFORM DTC CONFIRMATION PROCEDURE

1. Set the vehicle to READY.
2. Turn the MAIN switch of ProPILOT Assist 2.0 system ON.
3. Perform “All DTC Reading” with CONSULT.
4. Check if the “C1F76-49” is detected as the current malfunction in self-diagnosis results of “ICC/ADAS 2”.

Is “C1F76-49” detected as the current malfunction?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

1. CHECK DTC PRIORITY

If DTC “C1F76-49” is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#) (Without ProPILOT Assist 2.0) or [DTC Index](#) (With ProPILOT Assist 2.0).

NO>>

[GO TO 2.](#)

2. PERFORM SELF-DIAGNOSIS OF ABS ACTUATOR AND ELECTRIC UNIT (CONTROL UNIT)

Check if any DTC is detected in “Self Diagnostic Result” of “ABS”.

Is any DTC detected?

YES>>

Perform diagnosis on the detected DTC and repair or replace the malfunctioning parts. Refer to [DTC Index](#).

NO>>

Replace the ADAS control unit 2. Refer to [Removal and Installation](#) (Without ProPILOT Assist 2.0) or [Removal and Installation](#) (With ProPILOT Assist 2.0).

DTC DETECTION LOGIC

DTC		CONSULT screen terms (Trouble diagnosis content)	DTC detection condition	
C1F76	49	Steering angle sensor (Steering angle sensor)	Diagnosis condition	<ul style="list-style-type: none"> When vehicle is READY When MAIN switch of ProPILOT Assist system is ON
			Signal (terminal)	CAN communication signal
			Threshold	If the steering angle sensor is malfunction
			Diagnosis delay time	1 second or less

POSSIBLE CAUSE

- Steering angle sensor
- ADAS control unit 2

FAIL-SAFE

The following systems are canceled.

- Vehicle-to-vehicle distance control mode
- Conventional (fixed speed) cruise control mode
- Steering wheel assistance function
- AEB
- RAB
- I-FCW
- I-LI
- I-BSI
- TSR
- I-DA

CONFIRMATION PROCEDURE

1. CHECK DTC PRIORITY

If DTC "C1F76-49" is displayed with Network-DTC, first diagnose the Network-DTC.

Is applicable DTC detected?

YES>>

Perform diagnosis of applicable. Refer to [DTC Index](#).

NO>>

[GO TO 2.](#)

2. PERFORM DTC CONFIRMATION PROCEDURE

1. Set the vehicle to READY.
2. Turn the MAIN switch of ProPILOT Assist system ON.
3. Perform “All DTC Reading” with CONSULT.
4. Check if the “C1F76-49” is detected as the current malfunction in self-diagnosis results of “ICC/ADAS 2”.

Is “C1F76-49” detected as the current malfunction?

YES>>

Refer to [DTC Diagnosis Procedure](#).

NO-1>>

To check malfunction symptom before repair: Refer to [Intermittent Incident](#).

NO-2>>

Confirmation after repair: INSPECTION END

Sample